ONYX MODULAR 65MM THICK





ONYX MODULAR 65MM THICK



SPECIFICATIONS


Size (length x width x thickness)	200 x 98.5 x 65mm	Average Mass Per Paver	2.8kg
Nibbed	✓ If ticked, yes	Pavers Per Pallet	500
Chamfered	If ticked, yes	Typical 24 Hour Water Absorption	>6%
Factory Manufactured At	Springs, Gauteng	Exposure Zone Suitability	1-4
Pavers per m² (Excl cutting & watse)	48	Traffic	Medium Traffic
SANS	-	Dish Drain Channel	✓ If ticked, yes
ISO	9001:2015	Kerb End	✓ If ticked, yes
Average Compressive Strength	>53MPa	Bullnose on Flat	✓ If ticked, yes
Average Modulus of Rupture	>4MPa	Moisture Expansion Category	Category I



www.corobrik.co.za

THE ONYX RANGE







Download the high-resolution swatches, BIM files and view more project photos | www.corobrik.co.za

Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.

Information correct as at 2022/09/28 — www.corobrik.co.za