Firelight Satin FBX



CLASSIFICATION	FBX			
TEXTURE				
Choose clay face bricks for th	Bricks with a flat and even surface, providing a clean look with minimal texture. The information of the set of time with minimal effort.			

Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.

Firelight Satin FBX



SPECIFICATIONS

Size (width x length x height)	222 x 107 x 72mm	Classification	FBX
SANS	227:2007	ISO	9001:2015
Typical Compressive Strength	>43 MPa	Typical 24 ^{hr} Water Absorbtion	>10%
Moisture Expansion Category	11	Efflorescence Rating	Nil
Expoure Zone Suitability	1-3	Bricks per m² (excluding cutting & waste)	51
Factory Manufactured At	Midrand, Gauteng	Bricks per pallet	480
Average mass per brick	2.4kg	Available in Special Shaped Bricks	Yes
			www.corobrik.co.za

Download the high-resolution swatches, BIM files and view more project photos |

Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.

For image and project credits, please visit: <u>www.corobrik.co.za/featured-projects</u>

Information correct as at 28/06/2024