

Artisanal Vanilla FBX



CLASSIFICATION

FBX

TEXTURE

A rimped texture that gives you the appearance of an aged brick.

Choose clay face bricks for their unmatched durability, timeless beauty, and excellent thermal insulation, all while requiring no maintenance, ensuring your building stands the test of time with minimal effort.



Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.

Artisanal Vanilla FBX



SPECIFICATIONS

Size (width x length x height)	222 x 106 x 73mm	Classification	FBX
SANS	'-	ISO	'-
Typical Compressive Strength	>35 MPa	Typical 24^{hr} Water Absorbtion	>9%
Moisture Expansion Category	II	Efflorescence Rating	Slight
Expoure Zone Suitability	1-3	Bricks per m² (excluding cutting & waste)	51
Factory Manufactured At	Kwastina, Gauteng	Bricks per pallet	464
Average mass per brick	2.4kg	Available in Special Shaped Bricks	No



www.corobrik.co.za

Download the high-resolution swatches, BIM files and view more project photos | www.corobrik.co.za

Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.

For image and project credits, please visit: www.corobrik.co.za/featured-projects

Information correct as at 28/06/2024